

Calibration Request for Measuring Systems in terms of $N_{D,w}$ / N_K (Co-60 beam)



1. General Information

Customer <i>Name and full address</i>		
Contact person <i>Name, telephone, and e-mail</i>	Name:	
	Tel:	E-mail:

I would like to receive a quote.

2. Official Authorization

Name: Date: Signature:

Please fill and submit the form using the submit button or e-mail the file to service-emea@iba-group.com (subject: Calibration Request). Thank you for your request!

Comments:

The calibration certificate shall contain a recommendation on the calibration interval.

Note: According to DIN EN ISO/IEC 17025:2018 Chapter 7.8.4.3 a calibration certificate or calibration label shall not contain any recommendation on the calibration interval, except where this has been agreed with the customer. DIN EN ISO/IEC 17025:2018 is a German adoption of ISO/IEC 17025:2017.

The calibration will be performed according to the IAEA TRS-398/TRS-277, AAPM TG-51/TG-21, or DIN 6800-2 dosimetry protocols. Calibrations according to other national or international dosimetry protocols are available upon request.

The polarity and measuring range used during the calibration at the IBA SSDL are reported in the calibration certificate. If the instrument is used with a different polarity or measuring range from those listed in the calibration certificate, the user is advised to determine the effect of these differences and decide on their effects on the measurements. Additional information on these effects and ways to correct for them can be found in IAEA TRS-398."

Please include chamber build-up caps in case of air-kerma calibration. Please include waterproof sleeves in case of in-water calibration of non-waterproof chambers.

If you are sending radioactive check sources, please send also their leak-test certificates, a copy of the respective permit decision, and the appropriate chamber adapters.



3. Description of the Item to be Calibrated

Display device (electrometer, maximum 1):

Serial No	
Manufacturer	
Model/Type	

If your electrometer's manufacturer is other than IBA Dosimetry (or Scanditronics-Wellhöfer), please consider that we are not authorized to perform any repair or internal adjustment of the device.

If you are sending more than one electrometer, please submit a separate request for each electrometer and specify the chambers to be calibrated together with the electrometer in the respective request.

Ionization chambers

Chamber A

Manufacturer			
Model/Type			
Serial №			
Polarizing voltage and collecting electrode polarity	Polarizing voltage: _____ V	Collecting electrode polarity:	+ -
With/without electrometer calibration	calibration with the electrometer specified in paragraph 3.1	calibration without an electrometer	
Type of calibration	factory calibration	accredited calibration (SSDL)	

		SSD [cm]		Field size [cm ²]
Co-60	N_K <input type="checkbox"/>	$N_{D,w}$ <input type="checkbox"/>	100	10 × 10

Chamber B

Manufacturer			
Model/Type			
Serial №			
Polarizing voltage and collecting electrode polarity	Polarizing voltage: _____ V	Collecting electrode polarity:	+ -
With/without electrometer calibration	calibration with the electrometer specified in paragraph 3.1	calibration without an electrometer	
Type of calibration	factory calibration	accredited calibration (SSDL)	

		SSD [cm]		Field size [cm ²]
Co-60	N_K <input type="checkbox"/>	$N_{D,w}$ <input type="checkbox"/>	100	10 × 10

Chamber C

Manufacturer			
Model/Type			
Serial №			
Polarizing voltage and collecting electrode polarity	Polarizing voltage: _____ V	Collecting electrode polarity:	+ -
With/without electrometer calibration	calibration with the electrometer specified in paragraph 3.1	calibration without an electrometer	
Type of calibration	factory calibration	accredited calibration (SSDL)	

		SSD [cm]		Field size [cm ²]
Co-60	N_K <input type="checkbox"/>	$N_{D,w}$ <input type="checkbox"/>	100	10 × 10



Chamber D

Manufacturer			
Model/Type			
Serial №			
Polarizing voltage and collecting electrode polarity	Polarizing voltage: ___ V	Collecting electrode polarity:	+ -
With/without electrometer calibration	calibration with the electrometer specified in paragraph 3.1	calibration without an electrometer	
Type of calibration	factory calibration	accredited calibration (SSDL)	

		SSD [cm]		Field size [cm ²]
Co-60	N_K <input type="checkbox"/>	$N_{D,w}$ <input type="checkbox"/>	100	10 × 10

Chamber E

Manufacturer			
Model/Type			
Serial №			
Polarizing voltage and collecting electrode polarity	Polarizing voltage: ___ V	Collecting electrode polarity:	+ -
With/without electrometer calibration	calibration with the electrometer specified in paragraph 3.1	calibration without an electrometer	
Type of calibration	factory calibration	accredited calibration (SSDL)	

		SSD [cm]		Field size [cm ²]
Co-60	N_K <input type="checkbox"/>	$N_{D,w}$ <input type="checkbox"/>	100	10 × 10

e-mail the file to service-emea@iba-group.com (subject: Calibration Request)

